



# Click Studios

Passwordstate

RSA SecurID Configuration

# Table of Contents

<b>1</b>	<b>INTRODUCTION .....</b>	<b>3</b>
<b>2</b>	<b>CREATING AND INSTALLING SECURID CONFIGURATION FILES .....</b>	<b>4</b>
<b>3</b>	<b>TROUBLESHOOTING AUTHENTICATION ISSUES.....</b>	<b>7</b>

# 1 Introduction

This document will describe the process for initially configuring Passwordstate to use two-factor authentication with RSA's SecurID. It will also provide some guidance in troubleshooting authenticating users, as the response codes returned from an attempted authentication session can sometimes be unclear.

## IMPORTANT

When following the instructions in this document, you must be logged into the RSA Security Console with a user account which has 'Auth Mgr Agent Admin' rights.

## 2 Creating and Installing SecurID Configuration Files

Once Passwordstate is installed and operational, you must follow the steps below to create and copy across the SecurID configuration files. Please note these steps are based on RSA Authentication Manager 7.1 SP4 Patch 22, so the screens/instructions may be different for your version of Authentication Manager.

### Create Authentication Agent(s)

- Logon onto your Authentication Manager Security Console
- Navigate to the menu Access -> Authentication Agents -> Add New
- Select the appropriate Security Domain, specify the fully qualified Hostname of your Passwordstate web server, and click the 'Resolve IP Address' button to ensure DNS is working correctly

**RSA Security Console**

Home Identity Authentication Access Reporting RADIUS Administration Setup Help

### Add New Authentication Agent

Authentication agents provide a secure two-way communication path to and from the RSA Authentication Manager. When a user attempts to gain access to a network resource, the authentication agent authenticates the user and reports the result back to the RSA Authentication Manager.

Cancel Save Save & Add Another

\* Required field

#### Administrative Control

Security Domain: SystemDomain administrators may manage this authentication agent

#### Authentication Agent Basics

Hostname:  alien.halox.net  Existing node: -- Choose One --

IP Address:

Protect IP Address:  Prevent auto registration from unassigning IP address

Alternate IP Addresses:

IP Address

Notes:

#### Authentication Agent Attributes

Agent Type: Standard Agent

Disabled:  Agent is disabled

Agent May be Accessed by:  All users  Only members of user groups granted access to this agent

Authentication Manager Contact List:  Automatically assign automatic contact list from instance that responds first  Manually assign contact list: win2k3rsa1.halox.net (automatic)

#### Trusted Realm Settings

If the deployment uses trusted realms, specify which trusted users can access the authentication agent.

Trusted Realm Authentication:  Enable Trusted Realm Authentication

Cancel Save Save & Add Another

- Click on the 'Save' button

**Note 1:** You may need to specify different settings on this screen for your environment i.e. Enable Trusted Realm Authentication, etc.

**Note 2:** If you are using the High Availability Instance of Passwordstate, you will also need to create an Authentication Agent for your HA web server host name, and perform the same steps below for your HA web server installation.

### Create Node Secret

- Navigate to the menu Access -> Authentication Agents -> Manage Existing
- On the right-hand side of the Authentication Agent you just created, select 'Manage Node Secret' from the dropdown menu
- Click on the option 'Create a new random node secret, and export the node secret file'
- Specify an 'Encryption Password' to use, then click on the Save button
- Click on the 'Download Now' button, extract the zip file contents, and copy the files to the '/securid' folder in the Passwordstate web site

### Create and Install Configuration File

- Navigate to the menu Access -> Authentication Agents -> Generate Configuration File
- Specify any 'Agent Timeout and Retries' settings applicable to your environment
- Click on the 'Generate Config file' button
- Download the configuration file, extract the zip file contents, and copy the files to the '/securid' folder in the Passwordstate web site

## Generate the SecurID <no extension> File

- On your web server, open a command prompt with **Administrative Privileges**
- Change to the following folder c:\inetpub\passwordstate\securid\<32bit or 64bit>. The path to this folder may be different for your installation, and you will need to change to either the 32bit or 64bit operating system, depending on what Operating System Architecture you are using
- Type the command below, and enter the 'Encryption Password' you specified above when prompted. If the creation of the securid file is successful, you will see the message "The Node Secret is successfully loaded".  
agent\_nsload.exe -f c:\inetpub\passwordstate\securid\nodesecret.rec -d c:\inetpub\passwordstate\securid
- When the securid file is created, it is created without any owner or any NTFS permissions. To correct this, please follow these instructions:
  - Using Windows Explorer, right-click on the file and select 'Properties'
  - Click on the 'Security' tab and then on the 'Advanced' button
  - Click on the 'Continue' button
  - Click on the option 'Include inheritable permissions from the object's parent', then click on the 'Apply' button
  - Click on the 'OK' button and close all remaining open windows

**Note 1: It is important you fix the NTFS permissions on the securid file, otherwise the file cannot be backed up.**


**Note 2: Please wait at least 10 to 15 minutes before trying your first SecurID authentication in Passwordstate, as it can take a little time for the new Authentication Agent to be functional in RSA Authentication Manager.**

**Note 1:** If at any stage you decide to move your Passwordstate installation to a different web server with a different hostname/ip address, you will need to redo all these steps.

### 3 Troubleshooting Authentication Issues

There are multiple reasons why authentication can fail for a user, including an invalid `sdconfig.rec` file, or locked account, etc. Apart from error messages displayed in Passwordstate, the most effective means of determine what's causing the issue is my using the 'Real-Time Activity Monitors' feature in your Authentication Manager Security Console.

- Navigate to Reporting -> Real-Time Activity Monitors -> Authentication Activity Monitor
- Click on the 'Start Monitor' button, and retry your user authentication. Any errors or successful authentication attempts will now be displayed on the screen below. If you're still unable to determine what the cause is, please contact Click Studios and we will try to assist.



The screenshot shows the RSA Security Console interface. At the top left is the RSA Security Console logo. At the top right, it says "Logged in as: msand" with a "Close Window" link and "Realm: SystemDomain". The main heading is "Authentication Monitor" with a "Help on this page" link. Below the heading is a "Pause Monitor" button with a red arrow. A "Clear Monitor" button with a red 'X' is also present. The interface features a table with the following columns: Time, Activity Key, Description, Reason, User ID, Agent, Server Node IP, and Client IP. On the left side, there are several filter sections: "Display Results" with checkboxes for "Successful events", "Warning events", and "Failure events"; "Number of Results" with a dropdown set to 50; "User ID" with a "starts with" dropdown and an input field; "Authentication Agent" with a "starts with" dropdown and an input field; "Token Serial Number" with a "starts with" dropdown and an input field; and "Server Node" with a dropdown set to "win2k8rsa1\_server".

- If you see errors similar to 'Node secret mismatch: cleared on server but not on agent', or 'Node secret mismatch. Cleared on agent but not on server', then you may need to delete the 'Authentication Agent' you created, and redo all the steps above.